

OPTIČKI NIŠAN 4x32

ОПТИКА, ОПТИЧКИ НИШАНИ



Optički nišan 4x32 je namenjen za nišanje nepokretnih i pokretnih ciljeva pri gađanju iz automatske puške na daljinama do 500m danju, danju u uslovima smanjene vidljivosti i noću po vidljivim ciljevima. Opremljen je adapterom koji omogućava brzo i pouzdano montiranje nišana na pikatini šinu. Optički nišan 4x32 je konstruisan po ugledu na najpoznatije svetske proizvođače, modernog dizajna i proizveden je od najkvalitetnijih materijala što omogućava pouzdanu i dugotrajnu upotrebu u najekstremnijim uslovima.

Tehničke karakteristike	
Uvećanje	4x
Ugao vidnog polja	7°
Prečnik izlazne pupile	6 mm
Opseg rektifikacije nišana	±0-10
Udaljenost izlazne pupile	60 mm
Dioptrijsko podešavanje okulara	-0,5dptr do -1,5dptr
Rezolucija	do 15"
Skale daljine na končanici	100m, 300m, 500m
Opseg skale preticanja	±0-04
Temperaturno područje rada	od -30°C do +50°C
Osvetljenje končanice	LED
Izvor napajanja	Baterija 3 V CR2032
Minimalna autonomija rada	200h
Dimenzije	140x80x75mm
Masa sa nosačem	≤ 0,65kg



TELEOPTIK-ZIROSKOPI Elektro-opto mehanika, Filipa Višnjića 31, 11080 Beograd-Srbija
Tel: +381 11 2614 522 Tel/Fax: + 381 11 2105 439 E-mail: office@zioskopi.rs Web: www.zioskopi.rs

OPTICAL SIGHT 4x32

OPTICS, OPTICAL DEVICES



Optical sight 4x32 is designed for targeting fixed and moving targets at firing an automatic rifles at distances up to 500m by day, by day in low visibility conditions and at night by visible targets. It is equipped with an adapter that enables fast and reliable mounting of the sights on the picatinny rail.

Also, this sight meets all requirements of high precision; it has a practical use in extreme climatic and terrain conditions.

Technical features	
Magnification	4x
Field of view	7°
Exit pupil diameter	6 mm
Range of sight rectification	±0-10
Exit pupil distance	60 mm
Dioptric eyepiece adjustment	from -0,5dptr to -1,5dptr
Resolution	do 15"
Distance scale on reticle	100m, 300m, 500m
Range of overtaking scale	±0-04
Working temperature	od -30°C do +50°C
Reticle illumination	LED
Power supply	Baterija 3 V CR2032
Minimum work autonomy	200h
Dimensions	140x80x75mm
Mass	≤ 0,65kg



TELEOPTIK-GYROSCOPES Electro-opto mechanics, St Filipa Višnjića 31, 11080 Belgrade-Serbia

Tel: +381 11 2614 522 Tel/Fax: + 381 11 2105 439 E-mail: office@ziraskopi.rs Web: www.ziraskopi.rs